



DIN 2527

NW	D	Flange		Raised Face		Number	Bolts		Dia of Bolt Hole	Weight of One Flange (7.85 kg./ dm ³)	
		b	k	d4	f		Type - B kg	Type - C kg			
10	75	12	50	35	2	4	M10	--	11.5	0.38	0.33
15	80	12	55	40	2	4	M10	--	11.5	0.44	0.38
20	90	14	65	50	2	4	M10	--	11.5	0.65	0.59
25	100	14	75	60	2	4	M10	--	11.5	0.82	0.74
32	120	14	90	70	2	4	M12	(1/2")	14	1.17	1.07
40	130	14	100	80	3	4	M12	(1/2")	14	1.39	1.21
50	140	14	110	90	3	4	M12	(1/2")	14	1.62	1.43
65	160	14	130	110	3	4	M12	(1/2")	14	2.44	2.21
80	190	16	150	128	3	4	M16	(3.8")	18	3.43	3.09
100	210	16	170	148	3	4	M16	(5/8")	18	4.76	4.37
125	240	18	200	178	3	8	M16	(5/8")	18	6.11	5.68
150	265	18	225	202	3	8	M16	(5/8")	18	7.51	7.02
175	295	20	255	232	3	8	M16	(5/8")	18	10.4	9.85
200	320	20	280	258	3	8	M16	(5/8")	18	12.3	11.7
250	375	22	335	312	3	12	M16	(5/8")	18	18.3	17.6
300	440	22	395	365	4	12	M20	(3/4")	23	25.3	24.0
350	490	22	445	415	4	12	M20	(3/4")	23	31.6	30.1
400	540	22	495	465	4	16	M20	(3/4")	23	38.4	36.4
500	645	24	600	570	4	20	M20	(3/4")	23	60.4	58.1
200	340	24	295	268	3	8	M20	(3/4")	23	16.5	15.6
250	395	26	350	320	3	12	M20	(3/4")	23	24.0	23.1
300	445	26	400	370	4	12	M20	(3/4")	23	30.9	29.4
350	505	26	460	430	4	16	M20	(3/4")	23	40.6	38.0
400	565	26	515	482	4	16	M24	(7/8")	27	49.4	47.5
500	670	28	620	585	4	20	M24	(7/8")	27	75.0	72.7
10	90	14	60	40	2	4	M12	(1/2")	14	0.63	0.56
15	95	14	65	45	2	4	M12	(1/2")	14	0.72	0.64
20	105	16	75	58	2	4	M12	(1/2")	14	1.01	0.93
25	115	16	85	68	2	4	M12	(1/2")	14	1.23	1.13
32	140	16	100	78	2	4	M16	(5/8")	18	1.80	1.65
40	150	16	110	88	3	4	M16	(5/8")	18	2.09	1.85
50	165	18	125	102	3	4	M16	(5/8")	18	2.88	2.59
65	185	18	145	122	3	4	M16	(5/8")	18	3.66	3.33
80	200	20	160	138	3	*4/8	M16	(5/8")	18	4.77	4.34
100	220	20	180	158	3	8	M16	(5/8")	18	5.65	5.26
125	250	22	210	188	3	8	M16	(5/8")	18	8.42	7.67
150	285	22	240	212	3	8	M20	(3/4")	23	10.4	9.85
175	315	24	270	242	3	8	M20	(3/4")	23	14.0	13.5
200	340	24	295	268	3	12	M20	(3/4")	23	16.1	15.6
250	405	26	355	320	3	12	M24	(7/8")	27	24.9	23.9
300	460	28	410	378	4	12	M24	(7/8")	27	35.1	33.6
350	520	30	470	438	4	16	M24	(7/8")	27	47.8	46.2
400	580	32	525	490	4	16	M27	(1")	30	63.5	61.5
500	715	32	650	610	4	20	M30	(1.1/8")	33	102	99.5

ND - 6

ND - 10

Note : From 10mm to 175 mm see ND - 16

ND - 16

Note : For DIN 2527 ND 10 4 Holes